



中国船级社
CHINA CLASSIFICATION SOCIETY

证书编号/Certificate No.
AT25PTB00002

型式认可证书
CERTIFICATE OF TYPE APPROVAL

兹证明本证书所述制造厂具备按照下列标准的要求生产本证书所列产品的能力和条件。

This is to certify that the manufacturer stated in the certificate meets the requirements of the standards listed below and is available with the ability and conditions to produce the products described in the certificate.

制造厂/Manufacturer

玛努利液压器材（苏州）有限公司
Manuli Hydraulics (Suzhou) Co.,Ltd.

地址/Address

中国江苏省苏州工业园区杏林街85号
No.85 Xinglin Street, Suzhou Industrial Park, Jiangsu Province, P.R.China

产品名称/Product

挠性软管组件
Flexible Hose Assembly

认可标准/Approval Standard

1. 中国船级社《钢质海船入级规范》第3篇第2章
Chapter 2, Part Three of China Classification Society Rules for Classification of Sea-Going Steel Ships

用于/Intended for

船舶/Ships

产品明细/Product Description

其他管系产品/Other Piping System Product (M0001)

名称/Name	属性（值）/Value	单位/Unit
规格/Specification	Refer to the attachment Refer to the attachment	
型式 /Type	Refer to the attachment Refer to the attachment	
公称压力/Nominal Pressure	Refer to the attachment Refer to the attachment	Bar
设计温度/Design Temperature	Refer to the attachment Refer to the attachment	℃
外径/Outer Diameter	Refer to the attachment Refer to the attachment	mm

证书有效期至/This Certificate is valid until 2031年09月29日/ Sep. 29,2031

发证机构/Issued by 中国船级社烟台分社
CHINA CLASSIFICATION SOCIETY Yantai Branch

签发日期/Date 2026年09月30日
Sep. 30,2026

本证书根据中国船级社规范和相关规定签发。所有证书页为一个整体，必须同时使用。纸质证书每页均须由本社盖章方为有效，电子证书含数字签名方为有效，本证书复印件无效。任何单位和个人均不应摘录或节选本证书的部分内容。有关方对所持证书的真实性有疑问时，可以向我社检验机构咨询。本证书凡是未注明版本的规范，其（发证时）最新版本适用于本证书。
This Certificate is issued pursuant to the Rules of the Society and related regulation. All pages of the certificate are taken as a whole and are used simultaneously. No paper certificate page is valid without bearing the stamp of the Society, no electronic certificates is valid without the digital signature, and no copied form of the certificate is regarded as valid. Any part of the certificate is not to be extracted or abridged by any unit or individual in any form. Related parties who are doubted about the authenticity of the certificate may inquire of the Society or its offices. For Rules with no version indication, their latest version (at the time of issuance of the certificate) applies to the certificate.



Form No: T01.

联系方式/Contact Us, 见本社官方网站/See official web site of the Society (<http://www.ccs.org.cn>)

UTN:P026-03469044

批准的图纸/Approved Drawings

图纸批准号/ Drawings Approval No. : NP25PPP02937

产品认可试验报告/ Approval Test Report

试验报告编号/ Test Report No. : ZLA2503042

试验报告日期/ Test Report Date : 2025-07-23

试验报告编号/ Test Report No. : ZLB001080526

试验报告日期/ Test Report Date : 2026-05-08

试验报告编号/ Test Report No. : ZLB002080526

试验报告日期/ Test Report Date : 2026-05-08

试验报告编号/ Test Report No. : 20260610-001~015

试验报告日期/ Test Report Date : 2026-06-10

试验报告编号/ Test Report No. : 20260515-001;20260615-001;20260528-001;20260701-001;20260615-002;20260622-001;20260520-001;20260626-001;20260625-001;20260629-001

试验报告日期/ Test Report Date : 2026-07-01

认可后的产品检验方式/ Method of Product Inspection after Approval

按规范认可后应进行产品检验的产品/The product should be inspected in term of the rules:

认可后的产品检验应由本社验船师根据本社规范规定按批准的产品检验计划进行检验，经检验合格后由本社颁发船用产品证书。

After approval, product inspection should be carried out by the Surveyor of the Society in accordance with the approved product inspection scheme, and the Marine Product Certificate will be issued by the Society upon satisfactory inspection.

认可保持条件/ Maintenance Requirements of Approval

1. 型式认可后，如果产品及其重要零部件的设计、所用材料或制造方法有所改变，且影响到产品的主要特性、特征；或产品的性能指标有所更改，且超过认可的范围，则有关图纸和文件应经检验机构审批。并在检验机构认为必要时，经本社检验人员见证有关试验和进行检查，其结果应能证实仍符合认可条件。

After type approval, if there are changes to the design, materials used or manufacturing method of the product and important components and such changes affect major characteristics and properties of the product, or property indexes of the product are changed and exceed the scope of approval, related drawings and documents are to be examined and approved by the concerned survey office. Where deemed necessary by the survey office, the surveyor to the Society will go to witness relevant tests and conduct inspection and the results should be able to demonstrate compliance with the approval conditions.

2. 工厂的质量管理体系应保持有效运行，并且与认可时一致。如果质量管理体系发生改变，应经原体系认证机构审核并报本社批准。

The quality management system of the factory shall be ensure effective operation, and shall be the same as the situation of approval. If there are any changes to the quality management system, auditing of the original certification organization for quality management system and the society's approval shall be obtained.

3. 认可证书有效期内，如果出现可能导致本社取消认可的情况，工厂应及时采取有效的纠正措施。

Within the validity of the approval certificate, if cases occur that may cause the Society to withdraw the approval, the manufacturer should take corrective actions in a prompt and effective manner.

4. 在认可证书有效期内，本社检验人员可在未经事先通知的情况下对工厂的产品制造过程进行审核，以验证产品的生产是否符合业经本社批准的图纸和文件。工厂应予以配合。

Within the validity of the approval certificate, the surveyor to the Society may pay unannounced audit to the manufacturing process of the product in order to confirm whether it is in compliance with the drawings and documents approved by the Society. The factory should provide an active cooperation and necessary for the surveyor.

备注/Remarks

本社已审核了产品厂无石棉声明，但本社的审核不免除产品厂按照合同关系向订货方保证产品无石棉的责任。

The declaration of asbestos-free submitted by manufacturer has been reviewed by the Society.

However, liability of the manufacturer to guarantee the products are asbestos-free to purchaser

under contract will not be exempted.

中国船级社雅典分社

CCS Athens Branch

注：本证书含有附页，共1页

Note: The certificate is attached with additional 1 page(s)

No.	Hose Type	Size DN (mm)	Reinforcement Structure	Temperature Rage (°C)	Maximum Working Pressure (bar)	Fitting	Fire Resistance type
1	H5000D	12	4 Layers Spiral	-40°C~121°C	350	T7000	Fire Resistance Type
		16					
		19					
		25					
		31					
		38	6 layers Spiral				
2	T4000D	10	2 layers Braid	-40°C~100°C	280	T2000	Fire Resistance Type
		12					
		16					
		19					
3	T5000D	6	2 layers Braid	-40°C~100°C	350	T2000	Fire Resistance Type
		8					
		10					
		12					
4	T1D	5	1 layer Braid	-40°C~100°C	250	T2000	Fire Resistance Type
		6			225		
		8			215		
		10			180		
		12			160		
		16			130		
		19			105		
		25			90		
		31			65		
		38			50		
		51			40		
5	T2D	6	2 layers Braid	-40°C~100°C	420	T2000	Fire Resistance Type
		8			350		
		10			350		
		12			350		
		16			250		
		19			215		
		25			175		
		31			140		
		38			100		
		51			90		